

Comparisoon of selected 11.5" movements for interchangeability													
manufacturer	Miyota	Hangzhou	Nanning	Dixmont	Dixmont	Seagull	Seagull	Seagull	ETA	ETA	ETA	Soprod	Sellita
model	8215	HZ6300	NN2813 NN3813	DG2813 DG3813	DG4813	ST-1812 (TY2806)	ST-1812 (TY2661)	ST-2130 (TY2130)	2870/71/72 2873/78/79	2824-2	2892A2	A-10	SV-200
size/diameter	26mm overall*	26mm overall*	26mm overall*	26mm	26mm overall*	26mm overall*	26mm overall*	26mm	26mm	26mm	26mm overall*	26mm overall*	26mm overall*
height	5.67mm	4.6mm	5.45mm	5.45mm	5mm	5.76mm	3.6mm	4.6mm	5.3mm	4.6mm	3.6mm	4.6mm	4.6mm
stem height	2.5mm	1.8mm	2.5mm	2.5mm	1.8mm/2.5mm (TBC!!!)	2.5mm	1.5mm	1.8mm	2.5mm	1.8mm	1.5mm	1.8mm	1.8mm
hand sizes	100/152/17	90/150/25	100/150/17	100/150/17	100/150/17	100/150/17	90/150/25	90/150/25	90/150/25	90/150/25	90/150/25	90/150/25	90/150/25
dial feet position	around "25" and "50"	around "12" and "42"	around "28" and "54"	around "28" and "54"	around "25" and "55"	around "28" and "54"	around "12" and "42"	around "12" and "42"	around "12" and "42"	around "12" and "42"	around "12" and "42"	around "12" and "42"	around "12" and "42"
type	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic	automatic
date	yes	yes	yes	yes	yes	yes	yes	yes	yes*	yes	yes	yes	yes
date adjust	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset	quickset
jewels	21		22	22	22	21	21	26		17/21	17/21	25	26
power reserve (hours)	45		41	41			41	41	44	38	42	38	38
beat frequency hour (bph)	21.600	28.800	21.600	21.600	28.800	21.600	28.800	28.800	28.800	28.800	28.800	28.800	28.800
hacking (second stop)	no	yes	yes	yes	yes	yes	yes	yes	optional	yes	yes	yes	yes
shock absorber	Parashock					Novodiac	Incabloc	Novodiac	KIF, Incabloc, Novodiac	KIF, Incabloc, Novodiac	KIF, Incabloc, Novodiac	Incabloc	Novodiac
regulation							4 positions	2 positions		2 positions	4 positions	4 positions	2 positions
origin	Japan	China	China	China	China	China	China	China	Swiss	Swiss	Swiss	Swiss	Swiss
remarks	Hands will fit all Asian 100/150/17	2824 clone	Identical to DG2813 DG3813	Identical to NN2813 NN3813	Two versions available with different hour wheel, cannon pinion, seconds pinion etc to adjust for spacer height	Miyota 8205/8215 clone	2892 clone	2824 clone	287x series does not hack. Feature requires additional P/N A/7071 (Balance Stop Lever #9433); *2870 dateless			2824 clone	2824 clone

26mm overall = 11.5" lignes and nominal diameter of 25.6mm

[www.watch-tool.de](http://www.watch-tool.de) – [www.ouils-horloger.de](http://www.ouils-horloger.de) – [www.relojero-herramientas.es](http://www.relojero-herramientas.es) – [www.ferramentas-relojeiro.com](http://www.ferramentas-relojeiro.com) – [www.attrezzi-orologiaio.de](http://www.attrezzi-orologiaio.de)

© [www.uhrenwerkzeug.com](http://www.uhrenwerkzeug.com)